Distance between distribution boxes and substations



Overview

How It Works: Electric Transmission & Distribution and Protective The focus of this primer is on the transmission and distribution segments: the power line.

Key Takeaways

Distribution boxes are typically located within a few hundred feet to a few kilometers from substations, depending on voltage levels, feeder design, and safety requirements.

Typical Distances and Layout Considerations

The distance between a substation and distribution boxes (or distribution substations) depends on several factors, including voltage level, load density, and safety regulations. For 11 kV feeder lines, distribution substations are often placed around 300 feet (approximately 100 meters) from residential areas to ensure safety from electromagnetic fields and high-voltage equipment. In urban or high-density areas, distribution boxes may be closer to end users, while in rural areas, distances can extend to several kilometers to optimize feeder coverage.

Voltage and Feeder Design

Substations step down high transmission voltages (e.g., 115 kV, 230 kV) to distribution voltages suitable for local delivery, typically ranging from 11 kV to 33 kV. Distribution feeders carry this lower voltage to transformers near customer sites, which then supply secondary circuits. The placement of distribution boxes is designed to minimize voltage drop, reduce line losses, and maintain reliable service.

© 2026 DOLPHIN FIBER SYSTEMS - All rights reserved

IEE

E guidelines recommend careful planning of feeder lengths and spacing to balance efficiency and cost.

Safety and Regulatory Considerations

Safety distances are critical to protect both the public and maintenance personnel. Substations and distribution boxes must maintain minimum clearances from residential areas, roads, and other structures, often around 300 feet (100 meters) or more for medium-voltage feeders. These distances account for electromagnetic field exposure, arc flash hazards, and operational safety.

Additionally, proper layout ensures easy access for maintenance, inspection, and emergency response.

Practical Implementation

Urban areas: Distribution boxes are closer to end users, typically within a few hundred meters of the substation, to serve dense loads efficiently. Rural areas: Distances can extend to 1–3 km or more, depending on terrain and load distribution. Feeder design: Multiple feeders may branch from a substation to cover different zones, with distribution boxes strategically placed to maintain voltage stability and reduce losses.

Redundancy: Critical circuits often have duplicate feeders or backup distribution boxes to ensure reliability during maintenance or faults. In summary, the distance between substations and distribution boxes is a balance of electrical efficiency, safety, and practical layout, typically ranging from hundreds of feet in urban settings to several kilometers in rural areas, guided by IEEE standards and local regulations.

Article Content

How It Works: Electric Transmission & Distribution and Protective

The focus of this primer is on the transmission and distribution segments: the power lines, substations, and other infrastructure needed to move power from generation sources to end users.

Design guidelines for substation and power distribution systems of ...

Generally, the higher the distribution voltage, the farther apart substations may be located. However, they become larger in capacity and in number of customers served as distance apart

Substation Near Me – Find Electrical Substations on an Interactive Map

© 2026 DOLPHIN FIBER SYSTEMS - All rights reserved

Find electrical substations near any location on an interactive map. Search by voltage, operator & state. Free substation finder — no account needed.

Distribution Substations

Transmission substations can range from simple to complex. The large transmission substations can cover a large area (several acres/hectares) with multiple voltage levels, many circuit breakers and a

GUIDELINES FOR SUBSTATION AND SWITCHROOM ⋆ Archi

In case of two transformers (dry type or transformers with oil quantity less than 2000 litre) located next to each other without intermittent wall, the distance between the two shall be minimum 1500 mm for 11

11KV Clearance Requirements in Substations

This document provides guidelines on minimum clearance requirements and standards for electrical substations. It outlines clearance distances for phases, equipment, and live parts from the ground at

Distribution Substation

The connection between distribution networks and transmission or subtransmission occurs at distribution substations. Distribution substations have transformers to step voltage down to the primary

SPACING CONSIDERATIONS BETWEEN SUBSTATION

Surprisingly, there are no prescriptive mandatory national statutes requiring minimum distances between transformers and substations. On the one hand, the authors share the opinion that compliance with

How Power Grids Work

Transmission Substation The three-phase power leaves the generator and enters a transmission substation at the power plant. This substation uses large

Electric and magnetic fields from final distribution substations | EMFs

Final distribution substations always comply with the public EMF exposure guidelines. Electric fields Electric fields are very easily shielded and any final distribution substation within a building or

Substation Design Principles

The telecommunications panels shall be located in the substation control room, adjacent to the SCADA RTU panels. The telecommunications panel shall include equipment such as multiplexers, routers,

© 2026 DOLPHIN FIBER SYSTEMS - All rights reserved

Buying an EMF Safe Property

If you have a property, or decide to buy a property near a substation, plant thorny bushes between the nearest part of the plot and the substation to keep family members (and animals) at a safe distance.

ES352 Design of Distribution Substations and Transforming Points

In distribution substation buildings, noise emission will come principally from substation ventilators. Where noise complaints may arise due to noise emission from substation ventilators, space shall be

IEEE 525-2007_accepted

1.2 Purpose The purpose of this guide is to provide guidance to the substation engineer in established practices for the application and installation of metallic and optical cables in electric power

Substations – Volume II

The distribution substations discussed are generally limited to the traditional type characterized by simple bus arrangements and minimal equipment. However, the arrangements can be expanded for

Safety Clearance for Indoor & Outdoor Power Distribution Equipment

In the substation layout, the safety clearance between distribution devices refers to the minimum distance maintained between distribution devices or between distribution devices and other

Secondary LV/MV distribution substations in a nutshell

MV/LV distribution substations 1. General The space requirements of a substation depend on the equipment to be housed, and on whether a new

Modern practice for LV/MV substation and power distribution ...

Modern Practice for Buildings In the present era, the presence of reliable and uninterrupted electricity is commonly assumed in the majority of nations. Nevertheless, in many

© 2026 DOLPHIN FIBER SYSTEMS - All rights reserved

Contact Us

Continue your research online:

Website: https://dolphinspreschool.co.za
Technical inquiry: https://dolphinspreschool.co.za/project-desk.html
African project coordination: Waterfall City, Midrand, Gauteng, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 DOLPHIN FIBER SYSTEMS - All rights reserved