Optical module a0h



Overview

The 256 bytes of A0h mainly contain identification information about the optical module, including basic module details such as manufacturer name, manufacturer model, serial number, connector type, wavelength, transmission distance, and production date. As a universal photoelectric conversion module, the SFP optical module has uniform specifications for its structure, hardware and software to ensure broad compatibility with a wider range of host devices. Through a standardized I²C memory map, network devices can retrieve real-time telemetry such as module temperature, supply voltage, transmit bias current, and. ABSTRACT: This specification defines an enhanced digital interface (memory map and management interface) for monitoring and control of SFP+ optical transceivers and similar products.) ships with a small EEPROM that stores two kinds of information: a fixed Serial-ID block (vendor, part number, serial number, capabilities) and—when provided—a diagnostics area (real-time temperature, voltage, TX/RX power, etc. In block A0h (256bytes) first 128bytes (00h – 7Fh) are for serial ID and vendor information. It may be write protected (password may be required). (Note: the DDMI also applies to legacy GBIC optical transceivers.

© 2026 DOLPHIN FIBER SYSTEMS - All rights reserved

Article Content

Brief Introduction To The Data Structure Of SFP Optical Modules

Description of the A0h Data Structure. The 256 bytes of A0h mainly contain identification information about the optical module, including basic module details such as manufacturer name,

SFF-8472 Compliance: Mastering Optical Telemetry

Master SFF-8472 compliance for predictive optical monitoring. Learn to analyze A0h/A2h memory maps, monitor Tx Bias Current, and troubleshoot I2C bus lockups.

SFF-8472 Specification for Management Interface for SFP+

ABSTRACT: This specification defines an enhanced digital interface (memory map and management interface) for monitoring and control of SFP+ optical transceivers and similar products. The user''s

How to Read SFP & QSFP EEPROM Data — Practical

A0h (0xA0) — the serial ID / base EEPROM (96–128 bytes depending on form factor). You''ll find identifier, connector type, vendor name (bytes 20–35), vendor

Memory organization in SFP, QSFP, XFP and OSFP transceivers

QSFP/QSFP+ contains only block A0h (256 bytes) divided into pages (byte 7Fh in block A0h is page select byte). Pages are 128bytes length. Page 00h is required and provides static

Digital Diagnostic Monitoring Interface for SFP and SFP+ Optical ...

The SFP MSA section uses the two wire serial bus address 1010000X (A0h) and the enhanced interface uses 1010001X (A2h) to provide diagnostic information about the module''s present operating conditions.

SFF-8472: Management Interface for SFP+ Specification Rev 12

Abstract: This specification defines an enhanced digital diagnostic monitoring interface for optical transceivers which allows real time access to device operating parameters. This specification is

CMIS Common Management Interface Specification

Being an industry group uniting representatives of the data and optical worlds, OIF''s purpose is to accelerate the deployment of interoperable, cost-effective, and robust optical

Management Interface For SFP+: Published SFF-8472

© 2026 DOLPHIN FIBER SYSTEMS - All rights reserved

If the content of byte 13d of A0h is set 0Eh and bit 64.3 of page A0h is set to 1, bits 110.3 and bits 118.3 control the locking modes of the internal retimer or CDR.

Optical Module Development Platform 2.5 Gbps Transmitter with

Address A0h contains the serial ID information and other static information regard-ing the module that the vendor specifies (Table I). This is used to support the basic GBIC requirements and the extended

What Is Optical Module Coding Compatibility?

Optical module coding can be regarded as a key to match a switch, which is like a large lock. There are numerous switch brands, such as Cisco,

AFBR-89CEHZ Data Sheet

Description The Broadcom® AFBR-89CEHZ is a four-channel, pluggable, multimode, fiber optic QSFP28 transceiver for 100 Gigabit Ethernet (GbE) applications. The transceiver is a high

Optical module

Optical modules can either plug into a front panel socket or an on-board socket. Sometimes the optical module is replaced by an electrical interface module that implements either an active or passive

Quick Reference Guide for Programming the DS1873 SFP+ Controller

Auxiliary memory (device A0h) contains 256 bytes of EEPROM accessible from address 00h–FFh. The auxiliary memory is selected with the device address of A0h. Refer to the tables below for more

The Most Comprehensive Guide Of Optical Modules

Explore the ultimate guide to optical modules. Learn types, functions, performance metrics & how to choose the right module for your fiber network.

10G SFP+ Active Optical Cable (AOC)

Description FS SFP+ Active Optical Cable (AOC) assemblies use active circuits to support longer distances than standard Passive or Active SFP+ Copper Cables. They are designed for high speed,

Overview of the Development of Fiber Optic Transceivers

Fiber optic transceiver, also called optical module, is used to realize the conversion between electrical and optical signals.

DS1864 DS

© 2026 DOLPHIN FIBER SYSTEMS - All rights reserved

General Description The DS1864 is an SFF-8472 multisource agreement (MSA)-compliant laser controller/monitor that is ideal for SFP optical-transceiver module designs. It controls laser driver bias

Contact Us

Continue your research online:

Website: https://dolphinspreschool.co.za
Technical inquiry: https://dolphinspreschool.co.za/project-desk.html
African project coordination: Waterfall City, Midrand, Gauteng, South Africa

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 DOLPHIN FIBER SYSTEMS - All rights reserved